Creating a Monitoring Zone with Child Devices

Last Modified on 06/09/2025 3:52 pm EDT

Creating a Monitoring Zone with Child Devices

Procedure Steps

From System Administration, complete the following steps:

- 1. From the *Monitoring* menu, select *Monitor Zones*.
- 2. Select the Access Panel that is the Parent to the desired Child Device.
- 3. Change the Include All Child Devices drop-down to Specify Child Devices Individually.

CONT.							
Access Panels	•	Defaul	t Map:		-		
Device	Segment		Device *	Event Routing Group	Children	Parent Device	Segment
2220	Default Segment		2220	None (All Events Always)	Specify	(sector server,	Default Segment
		Assign->	1				
		. Detter					
5		C-THENDYE					
opecity critic Lievic	es naviouely						
Event Routing G	roup						
None (All Eve	ents Always)						

- 4. Click [Assign].
- 5. Change the **Select** drop-down to the type of Child Device that needs to be added to the Monitoring Zone, such as Alarm Panels.
- 6. The Child Devices are now displayed in the list, making them available for assignment to the Monitoring Zone. In this case, the Child Devices include the Alarm Panels configured in the system.

Alam Panela 🔹			222					
Device	Parent Device	Segment	Default	Map:		*		
1100	2220	Default Same		Device	Event Routing Group	Children	Parent Device	Segment
1200	2220	Default Segmer		a 2220	None (All Events Always)	Specify		Default Segment
		[Assign->					
e(, (<-Remove					
ipecify Child Devic	es Individually	•						
Event Routing G	roup							
None (All Eve	nts Always)							

Applies To

OnGuard (All versions)

Additional Information

Note: To add Children for other Access Panels, add them by following the above steps.